# XYSIL®300

## **Hydrophilic Fumed Silica**

**XYSIL<sup>®</sup> 300** is a hydrophilic Fumed Silica with a specific surface area of 300m<sup>2</sup>/g, and also known as Synthetic, Amorphous Silica, manufactured by

a continuous flame hydrolysis process of silicon tetrachloride.

### Characteristic physico-chemical data

Properties	Units	Guarantee value	Standardization	
Specific surface area (BET)	m²/g	300±25	GB/T10722	
pH-value (in 4% dispersion)		3.8-4.5	GB/T1717	
Loss on drying, ex works( 2h @ 105℃)	wt%	<1.5	GB/T5211.3	
Loss on ignition(2h @ 1000,based on material dried for 2h @ 105 $^\circ$ C)	wt%	<2.5	GB/T20020	
Sieve residue (45µm)	%	<0.05	GB/T5211.14	
SiO_2 content (based on the substance heated at 1000 $^\circ\!\mathbb{C}$ for 2 h)	wt%	>99.8	GB/T20020	
Tamped density (based on material dried for 2h @ 105 $^\circ\!\!\!\!\!^{\rm C}$ )	g/L	25~60	GB/T5211.4	
Carbon content (based on material dried for 2h @ 105 $^\circ$ C)	wt%	<0.2	GB/T20020	
Appearance	Fine, white, amorphous powder			

At time of packaging.

#### **Application s and Properties**

#### Application:

- > HTV Silicone Rubber, Liquid Silicone Rubber
- > Paints and Coatings, Ink, Pigment
- Unsaturated polyester resins
- Adhesive & Sealant

#### Functions:

- Rheology and thixotropy Control
- Used as anti-settling, thickening, anti-sagging agent
- Free Flow and Suspension
- Reinforcement
- Excellent transparency

#### **Packaging and Storage**

XYSIL<sup>®</sup> 300 is packaged in multiple layer kraft paper 10kg bags or 180Kg FIBCs on pallet, and should be stored in the original packaging in dry storage areas for protecting the material from volatile substance, and should be used in two years after production.

#### Transportation:

20'GP: 1800KG, 10 pallets, 180KG/pallet. 40'GP: 3600KG, 20 pallets, 180KG/pallet. 40'HQ: 4000KG, 20 pallets, 200KG/pallet. Road Transportation: by requirement

### **Registrations(substance or product components)**

Chemical Name	CAS NO.	REACH(EU)	KKDIK	K-REACH	TSCA	Customs Tariff Number
Silicon Dioxide	112945-52-5, 7631-86-9	Registered	Registered	Registered	Registered	281122(Internet); 2811229000(China)

This information is supplied on basis of our best knowledge, as a convenience and for information purposes only. We disclaim any warranty and liability whatsoever as to accuracy and completeness of such information as well as to the potential infringement of any proprietary rights.

### Henan Xunyu Chemical Co.,Ltd.

Add: No.18, Shangwu Waihuan Road, Zhengdong New Dis, Zhengzhou City, Henan Province, P.R. China

Tel: +86-371-69176282 Fax: +86-371- 69176283

Email: info@xunyuchem.com; technique@xunyuchem.com; marketing@xunyuchem.com

Website: www.xunyuchem.com, www.fumed-silica.net, www.xysil.com

## Certificated by ISO9001 – ISO14001 – ISO45001 – SGS- REACH – KKDIK – K-REACH



# TECHNIQUE DATA SHEET