

XYSIL®380

Hydrophilic Fumed Silica

TECHNIQUE DATA SHEET

 $ilde{ t KYSIL}^{ ext{@}}$ $ilde{ t 380}$ is a hydrophilic Fumed Silica with a specific surface area of $ilde{ t 380}$ m 2 /g, and also known as Synthetic, Amorphous Silica, manufactured by

a continuous flame hydrolysis process of silicon tetrachloride.

Characteristic physico-chemical data

Properties	Units	Guarantee value	Standardization	
Specific surface area (BET)	m²/g	380±25	GB/T10722	
pH-value (in 4% dispersion)		3.8-4.5	GB/T1717	
Loss on drying, ex works(2h @ 105°C)	wt%	<1.5	GB/T5211.3	
Loss on ignition(2h @ 1000,based on material dried for 2h @ 105℃)	wt%	<2.5	GB/T20020	
Sieve residue (45µm)	%	<0.05	GB/T5211.14	
SiO₂ content (based on the substance heated at 1000 °C for 2 h)	wt%	>99.8	GB/T20020	
Tamped density (based on material dried for 2h @ 105℃)	g/L	25~60	GB/T5211.4	
Carbon content (based on material dried for 2h @ 105℃)	wt%	<0.2	GB/T20020	
Appearance	Fine, white, amorphous powder			

At time of packaging.

Applications and Properties

Application:

- > HTV Silicone Rubber, Liquid Silicone Rubber
- Paints and Coatings, Printing Inks
- Unsaturated polyester resins(UPR)
- Cable compounds
- > Adhesive & Sealant

Functions:

- > Rheology and thixotropy Control of polymers, liquids,etc
- > The highest surface area resulting in the best thickening
- Reinforcement of HTV Silicone Rubber
- High Transparency
- Flow aid

Packaging and Storage

XYSIL[®] 380 is packaged in multiple layer kraft paper 10kg bags or 180Kg FIBCs on pallet, and should be stored in the original packaging in dry storage areas for protecting the material from volatile substance, and should be used in two years after production.

Transportation:

20'GP: 1800KG, 10 pallets, 180KG/pallet. 40'GP: 3600KG, 20 pallets, 180KG/pallet. 40'HQ: 4000KG, 20 pallets, 200KG/pallet. Road Transportation: by requirement

Registrations(substance or product components)

Chemical Name	CAS NO.	REACH(EU)	KKDIK	K-REACH	TSCA	Customs Tariff Number
Silicon Dioxide	112945-52-5, 7631-86-9	Registered	Registered	Registered	Registered	281122(Internet); 2811229000(China)

This information is supplied on basis of our best knowledge, as a convenience and for information purposes only. We disclaim any warranty and liability whatsoever as to accuracy and completeness of such information as well as to the potential infringement of any proprietary rights.

Henan Xunvu Chemical Co..Ltd.

Add: No.18, Shangwu Waihuan Road, Zhengdong New Dis, Zhengzhou City, Henan Province, P.R. China

Tel: +86-371-69176282 Fax: +86-371- 69176283

Email: info@xunyuchem.com; technique@xunyuchem.com; marketing@xunyuchem.com

Website: www.xunyuchem.com, www.fumed-silica.net, www.xysil.com

Certificated by ISO9001 – ISO14001 – ISO45001 – SGS- REACH – KKDIK – K-REACH