

# XYSIL®R210

## **Hydrophobic Fumed Silica**

# **TECHNIQUE DATA SHEET**

**KYSIL** <sup>®</sup> **R210** is a structure modified hydrophobic Fumed Silica based on a hydrophilic fumed silica with a specific surface area of 230m2/g.

#### **Physico-chemical Data**

| Properties   | Units | Typical Value | Standardization |
|--|-------|---------------|-----------------|
| Specific Surface Area(BET)   | m2/g  | 210±20        | GB/T10722       |
| pH Value (in 4% dispersion)  |       | 7.0-8.5       | GB/T10722       |
| Loss on Drying, Ex Works ( 2h @ 105℃)                              | wt%   | <0.5          | GB/T1717        |
| Loss on ignition(2h @ 1000,based on material dried for 2h @ 105°C) | wt%   | <8.0          | GB/T5211.3      |
| Tamped density (based on material dried for 2h @ 105℃)             | g/L   | 40~60         | GB/T5211.14     |
| SiO2 content(based on the substance heated at 1000℃ for 2 h)       | wt%   | >99.8         | GB/T20020       |
| Carbon content(based on material dried for 2h @ 105℃)              | wt%   | 3.5-6.5       | GB/T5211.4      |

At time of packaging.

#### **Application s and Properties**

## Application:

- ♦ Paint&Coating
- ♦ RTV Silicone Sealant, Silicone Rubber,
- ♦ Adhesive

#### Functions:

As a thickening, thixotropic agent and anti-settling agent in coating, paint, adhesive, sealant and silicone ect.

#### **Packing and Storage**

XYSIL® R210 is packaged in multiple layer kraft paper 10kg bags on pallet, and should be stored in the original packaging in dry storage areas for protecting the material from volatile substance.

### **Transportation:**

Sea Transportation

20'GP: 1800KG, 10 pallets, 180KG/pallet. 40'GP: 3600KG, 20 pallets, 180KG/pallet. 40'HQ: 4000KG, 20 pallets, 200KG/pallet. Road Transportation: by requirement

This information is supplied on basis of our best knowledge, as a convenience and for information purposes only. We disclaim any warranty and liability whatsoever as to accuracy and completeness of such information as well as to the potential infringement of any proprietary rights.

### Henan Xunyu Chemical Co.,Ltd

Add: No.18, Shangwu Waihuan Road, Zhengdong New Dis, Zhengzhou City, Henan Province, P.R. China

Tel: +86 371 69176282 Fax: +86 371 69176283

Email: info@xunyuchem.com; technique@xunyuchem.com

Website: www.xunyuchem.com